KOREAN PATENT ABSTRACTS

(11)Publication number:

1020010017115 A

(43)Date of publication of application: 05.03.2001

(21)Application number: 1019990032464

(22)Date of filing:

(71)Applicant:

KOREA ADVANCED INSTITUTE

OF SCIENCE AND

TECHNOLOGY

(72)Inventor:

HAN, CHEOL HUI JUNG, HUN JU LEE, SEUNG U

(51)Int. CI

G09G 3/36

07.08.1999


(54) CIRCUIT OF DIGITAL DRIVING FOR LIQUID CRYSTAL DISPLAYER

(57) Abstract:

PURPOSE: A circuit of digital driving for a liquid crystal displayer is provided to reduce the number of data bus lines and data latches by managing the information about bits of the digital image information in order according to time.

CONSTITUTION: The device includes the first data latch(31), a shift register(33), the second data latch(32) and a digital/analog converter(34). The first data latch(31) stores the data of the digital image information in order through a data bus. The shift register(33) locks the operation of the first data latch(31) to the location of the digital image information input from the outside. The second data latch(32) stores the digital Information stored in the first data latch(31) before converting into analog. The digital/analog converter(34) inputs the data of the digital image information stored in the second data latch(32) in order each bit and converts them into the analog signal.

COPYRIGHT 2001 KIPO



© EPODOC / EPO

PN - KR20010017115 A 20010305

TI - CIRCUIT OF DIGITAL DRIVING FOR LIQUID CRYSTAL DISPLAYER

- PURPOSE: A circuit of digital driving for a liquid crystal displayer is provided to reduce the number of data bus lines and data latches by managing the information about bits of the digital image information in order according to time. CONSTITUTION: The device includes the first data latch(31), a shift register(33), the second data latch(32) and a digital/analog converter(34). The first data latch(31) stores the data of the digital image information in order through a data bus. The shift register(33) locks the operation of the first data latch(31) to the location of the digital image information input from the outside. The second data latch(32) stores the digital information stored in the first data latch(31) before converting into analog. The digital/analog converter(34) inputs the data of the digital image information stored in the second data latch(32) in order each bit and converts them into the analog signal.

EC - G09G3/36C14A

ICO - S09G213/14B

PA - KOREA INST SCIENCE TECHNOLOGY [KR]

IN - HAN CHEOL HUI [KR]; JUNG HUN JU [KR]; LEE SEUNG U [KR]

AP - KR19990032464 19990807

PR - KR19990032464 19990807

DT - II

FAMN- 19606506

- G09G3/36

ICAI - G09G3/36

ICCI - G09G3/36

LA - en

NPR - 1

OPD - 1999-08-07

PD - 2001-03-05

© WPI / Thomson

AN - 2001-606027 [69]

TI - Circuit of digital driving for liquid crystal display

AB - NOVELTY:

A circuit of digital driving for a liquid crystal display is provided to reduce the number of data bus lines and data latches by managing the information about bits of the digital image information in order according to time.

- DETAILED DESCRIPTION:

The device includes the first data latch(31), a shift register(33), the second data latch(32) and a digital/analog converter(34). The first data latch(31) stores the data of the digital image information in order through a data bus. The shift register(33) locks the operation of the first data latch(31) to the location of the digital image information input from the outside. The second data latch(32) stores the digital information stored in the first data latch(31) before converting into analog. The digital/analog converter(34) inputs the data of the digital image information stored in the second data latch(32) in order each bit and converts them into the analog signal.

IW - CIRCUIT DIGITAL DRIVE LIQUID CRYSTAL DISPLAY

PN - KR20010017115

A 20010305 DW200169

KR100345285B US6747625 B 20020725 DW200308 B1 20040608 DW200437

IC - G09G3/36

ICAI - G09G3/36

ICCI - G09G3/36

MC - T04-H03B T04-H03C2A

DC - P85 .

- T04

- PA (KOAD) KOREA ADV INST SCI & TECHNOLOGY
- IN CHUNG H; CHUNG H J; HAN C; HAN C H; JUNG H J; LEE S; LEE S U; LEE S W
- AP KR19990032464 19990807; US20000628040 20000727; [Previous Publ KR20010017115 A 00000000]
- PR KR19990032464 19990807

